

ExtremeALU Heat

Permanently elastic, heavy underlay with patented RWS Barrier base material, for extreme walking noise improvement and fantastic floor heating performance.



RWS Barrier base material defines a new standard for the highest walking noise improvement value. All tests were conducted by the EPH GmbH.

In addition to laboratory tests, end-user experience was confirmed in real life conditions as RWS performance compared to other premium range underlays on the market.

Product compatibility

- ✓ Commercial laminate and engineered floors.

Product highlights

- ✓ Outstanding floor heating compatibility.
- ✓ Unrivalled walking sound improvement (RWS) thanks to RWS Barrier.
- ✓ Integrated vapor barrier.



Innovation and quality made in Poland. Since 2007.

Member of



rev. 11/2024

Brandverhalten: normalentflammbar (Klasse E/Fl)
nach DIN EN 13501-1 oder Baustoffklasse DIN 4102-B2
Emissionsgeprüftes Bauprodukt nach DIBt-Grundsätzen.



Symbol	Category	Value	Unit	Limit	Test methods
T	Thickness	2,0	mm	+/- 0,20	EN823
L	Length	8 000	mm	-1/+ 5%	EN822
W	Width	1 000	mm	-1/+ 2,5%	EN822
AW	Area Weight	1,70	kg/m²	+/- 10%	EN ISO 23997:2012
QW	Density	875	kg/m³	+/- 10%	EN ISO 23996:2012
RWS	Reflected Walking Sound	<49,8	sone	+/- 2	EN 16205
IS	Impact Sound reduction	>19	dB	+/- 2	EN 16354:2018
CS	Temporary loads resistance	298	kPa	+/- 10	EN 16354:2018
CC	Static loads (furniture) resistance	>50	kPa	+/- 10	EN 16354:2018
DL	Dynamic loads (walking) resistance	>250 000	cycles		EN 16354:2018
PC	Local unevenness compensation	1,1	mm	+/- 10%	EN 16354:2018
TR	Thermal insulation	0,011	m²K/W	+/- 0,003	EN 16354:2018
SD	Protection against moisture	>75	m		EN 16354:2018
RLB	Protection against falling objects	800	mm		EN 16354:2018
RTF	Reaction To Fire	E _n			EN-ISO11925-2, PN-EN13501-1

Logistic Parameter	Sales Unit	Packaging	Pallet
Form	roll	Corrugated box	EUR
Quantity	1 Pc.	35 Pc.	1 corrugated box
Area	8 m²	280 m²	280 m²
Weight	13,28 kg +/- 10%	464,8 kg +/- 10%	464,8 kg +/- 10%

General information


All data are based on our experience and careful investigations. The diversity of the materials used, as well as the different construction site and processing conditions, can not be examined or influenced by us in detail. The quality and function therefore depends on the expert site evaluation and product use. In case of doubt, carry out your own tests or seek advice on our application technology. When processing, please observe the rules of technology as well as the manufacturing specifications of the building materials involved and constantly changing state of technology. Due to its composition and technology of production, this product may have a residual smell of natural rubber that disappears right after the assembly of the floor. This product has been tested and does not emit volatile organic compounds (VOC class A+).

Storage

Approx. 1 year, protecting from direct sunlight or other weather influences.

Application

Unroll underlay on the floor, aluminized side facing up, with individual panels adjacent to one another and seal the joints with aluminum sealing tape. Product informations may change without notice. Please visit our webpage for updated product informations.



EXTREME line

www.fairunderlay.com